


**NT 5511.5-2SW | POLYSIL YELLOW FUNCTIONAL SPLICING ADHESIVE TAPE | FILM TAPE**

**PolySil™ NT-5511.5-2SW is a polyester film tape with an easy release fluorosilicone coating on back side of PET and high temperature silicone adhesive on the other side. This tape is self-wound for easy splicing of siliconized webs. NT 5511.5-2SW has been designed for splicing of roll label stock and substrates to be coated with pressure sensitive adhesive.**

**FEATURES & BENEFITS**

- **Easy release coated PET**
- **Provides adhesive transfer at the splice area**
- **Excellent for sequential label application requirements**
- **Chemical and Abrasion resistant**
- **Good conformability**

**CONSTRUCTION DIAGRAM**



**TYPICAL APPLICATIONS**

- **Functional Splicing - label stock and adhesive transfer**
- **Covering of idlers / in process rolls**

**CONSTRUCTION**

**PERFORMANCE**

<b>1.5 mil fluorosilicone coated PET</b>
<b>1.5 mil silicone adhesive</b>
<b>Self wound</b>
<b>Yellow</b>

<b>Breaking Strength: lbs./inch (kg/cm)</b>	42 (7.3)
<b>Elongation:</b>	110 %
<b>Adhesion to steel: oz./inch (kg/cm)</b>	37 (.41)
<b>Dielectric Strength:</b>	5,900 Volts
<b>Temperature Range:</b>	-60°F to 350°F (-51°C to 177°C)

**IMPORTANT NOTICE TO PURCHASER:** All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**

©2009 Adhesive Applications, Inc.