


NT 580 | RED SILICONE ADHESIVE PLATERS TAPE | FILM TAPE

NT 580 is a red silicone polyester tape with controlled adhesion and good conformability for sharp line definition in etching and plating operations. The controlled level of cross-linking assures a proper balance of adhesion to substrates, chemical resistance and clean removal with no residue. The tape is unique in that the adhesive system is translucent on the polyester and allows the operator to make precision alignments easily.

FEATURES & BENEFITS

- Fine line definition
- Clean removal / No adhesive residue
- Chemical and Abrasion resistant
- Good conformability

CONSTRUCTION DIAGRAM



TYPICAL APPLICATIONS

- Solder Strip bath
- Precious metal plating
- Electrical insulations
- Splicing – silicone coated paper, films, textiles

CONSTRUCTION

1 mil PET backing
3 mil cross-linked silicone adhesive
Self wound
Red

PERFORMANCE

Breaking Strength: lbs./inch (kg/cm)	35 (6.3)
Elongation:	130 %
Adhesion to steel: oz./inch (kg/cm)	35 (.40)
Dielectric Strength:	5,400 Volts
Temperature Range:	-60°F to 350°F (-51°C to 177°C)

Conformance to circuit board requires application of firm pressure with rubber covered rollers by hand or machine. A heat assist may be employed in laminating. Components requiring critical alignment can be machine laminated after hand alignment.

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**