


NT 500 | POLYSIL WHITE SILICONE ADHESIVE TAPE | FILM TAPE

PolySil™ NT 500 consists of electrical grade polyester coated with silicone adhesive. This protective mask removes cleanly with no adhesive residue. The film backing exhibits virtually no shrinkage after exposure to elevated temperatures. Used to protect a variety of substrates during fabrication, installation, handling and shipping.

FEATURES & BENEFITS

- **Fine line definition**
- **Clean removal / no adhesive residue**
- **No film shrinkage**

CONSTRUCTION DIAGRAM



TYPICAL APPLICATIONS

- Protective Mask
- Powder Coating
- Fume Masking

CONSTRUCTION

PERFORMANCE

5 mil PET backing
1.5 mil cross-linked silicone adhesive
Self wound
White

Adhesion to steel	16 -18 oz/inch
Elongation	>100%
Temperature Range:	-60°F to 350°F (-51°C to 177°C)

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**