

DEV 200GFR | GLASS FILLED RED ACRYLIC TRANSFER ADHESIVE TAPE | TRANSFER ADHESIVE TAPES


DEV 240GFR | GLASS FILLED RED ACRYLIC TRANSFER ADHESIVE TAPE | TRANSFER ADHESIVE TAPES

These glass filled unsupported red acrylic transfer adhesives exhibit excellent adhesion, shear properties and solvent resistance. DEV 200GFR and DEV 240GFR are formulated with a glass filled acrylic PSA that performs well in various splicing and transfer adhesive applications. The 76# white moisture stable liner is ideal for kiss cut applications and precision component assembly.

FEATURES & BENEFITS

- Excellent chemical resistance
- Excellent high temp performance
- Excellent shear strength

CONSTRUCTION DIAGRAM



TYPICAL APPLICATIONS

- Die cutting
- Precision component assembly
- Graphic Arts
- Splicing

CONSTRUCTION

5.5 mil white 76# poly-coated kraft liner

2 mil red glass filled acrylic adhesive – DEV 200GFR

4 mil red glass acrylic adhesive – DEV 240GFR

Self wound

PERFORMANCE

| PROPERTIES | DEV 200GFR | DEV 240GFR |
|---|------------|-------------|
| 180° Peel, 2 mil PET/ss: 20 min bond – | 72 oz/inch | 76 oz/inch |
| 180° Peel, 2 mil PET/ss: 72 hr dwell – | 82 oz/inch | 100 oz/inch |
| Shear, 1" x 1" x 1000g, 2 mil PET/ss: 10 min bond | 21+ days | 21+ days |

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**

©2009 Adhesive Applications, Inc.