

DEV 902GFR W61 | GLASS FILLED RED ACRYLIC TRANSFER ADHESIVE TAPE


DEV 902GFW61 | GLASS FILLED ACRYLIC TRANSFER ADHESIVE TAPE

DEV-902GFW61 and DEV-902GFRW61 are glass filled solvent acrylic transfer PSA's for use in various splicing and transfer adhesive applications.

FEATURES & BENEFITS

- Moderate adhesion
- Excellent low temp application performance
- Moderate shear strength

CONSTRUCTION DIAGRAM



TYPICAL APPLICATIONS

- Die cutting
- Precision component assembly
- Graphic Arts
- Splicing

CONSTRUCTION

5.5 mil white 76# poly-coated kraft liner

2 mil red glass filled acrylic adhesive – DEV 902GFRW61

2 mil clear glass acrylic adhesive – DEV 902GFW61

Self wound

PERFORMANCE

PROPERTIES	DEV 902GF	DEV 902GFR
180° Peel, 2 mil PET/ss: 20 min bond –	36 oz/inch	36 oz/inch
180° Peel, 2 mil PET/ss: 72 hr dwell –	76 oz/inch	62 oz/inch
Shear, 1" x 1" x 1000g, 2 mil PET/ss: 10 min bond	72+H	72+H

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**

©2009 Adhesive Applications, Inc.