

HLUP025 | PERMANENT LSE UNSUPPORTED TAPE | TRANSFER ADHESIVE TAPE

Specially formulated LSE permanent transfer tape with a paper liner that provides a high bond to low surface energy materials; such as polypropylene, polyethylene, plastic and UV coated products. The adhesive has been tested by an independent lab and approved for direct skin contact.


FEATURES & BENEFITS

- Available extended liner or flush cut
- Various length rolls
- Various widths starting at 1/2"
- Planetary wound

ROLLS PER CARTON

- 1/2" liner ~ 1/4" adhesive – 10 rolls
- 3/4" liner ~ 1/2" adhesive – 7 rolls
- 1" liner ~ 3/4" adhesive – 5 rolls

CONSTRUCTION DIAGRAM



TYPICAL APPLICATIONS

- Tyvek
- Labels ~ Envelopes
- Bags ~ Forms
- Posters ~ Signs

CONSTRUCTION

2.5 mil Rubber Adhesive
3.2 mil Black Printed EZ Release 53# Liner

PERFORMANCE

180° Peel Adhesion (PSTC 1) (after 24 hours)	96 oz/in
Shear Adhesion (PSTC 7)	30 hours
Loop Tack	80 oz/in
Application Temperature	40°F to 90°F
Service Temperature	0°F to 150°F

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**

©2009 Adhesive Applications, Inc.