


NT 140W76APS | 4 MIL CLEAR ACRYLIC TRANSFER ADHESIVE TAPE | TRANSFER ADHESIVE TAPES

This smooth, high performance, unsupported acrylic transfer adhesive has excellent permanent adhesion over a broad temperature range and superior long term aging characteristics. The adhesive is supplied on a moisture stable liner and has a smooth surface for faster substrate wet out. With the poly-coated kraft liner, NT 140W76APS can be used for kiss cut applications, photo mounting and precision component assembly.

FEATURES & BENEFITS

- Excellent chemical resistance
- Fast wet out
- Bonds well to glass, wood, steel, aluminum, ABS, styrene, vinyl and others
- Excellent shear strength

CONSTRUCTION DIAGRAM



TYPICAL APPLICATIONS

- Mounting
- Die cutting
- Precision component assembly

CONSTRUCTION

5.5 mil white 76# poly-coated kraft liner
4 mil acrylic adhesive
Self wound

PERFORMANCE

Adhesion to Aluminum - 90° Peel	75 oz/in 20 min wet out	112 oz/in 72 HR wet out
Adhesion to ABS - 90° Peel	95 oz/in 20 min wet out	127 oz/in 72 HR wet out
Creep resistance: 500g./0.25 sq. in	120 hours	
Temperature range	-40°F to 250°F (-54°C to 121°C)	
**Shear Adhesive Failure Temperature	240°F (115°C) Cohesive Failure	
**SAFT – 1" x 1" x 100gms PET/Film/ss		

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**

©2009 Adhesive Applications, Inc.