


NT 240W76APS | 4 MIL CLEAR ACRYLIC HIGH TEMP TRANSFER ADHESIVE TAPE | TRANSFER ADHESIVE TAPES

This high temperature unsupported acrylic transfer adhesive is designed for high performance in applications with elevated temperatures. Excellent adhesion, high temperature shear properties and solvent resistance are features of this adhesive. The 76# white moisture stable liner is ideal for kiss cut applications and precision component assembly.

FEATURES & BENEFITS

- Excellent chemical resistance
- Bonds to variety of substrates where temperature is critical
- Excellent shear strength

CONSTRUCTION DIAGRAM



TYPICAL APPLICATIONS

- High temperature splicing
- Interior automotive applications
- Die cutting
- Precision component assembly
- Photo mounting
- Graphic Arts

CONSTRUCTION

5.5 mil white 76# poly-coated kraft liner
4 mil acrylic adhesive
Self wound

PERFORMANCE

180° Peel, 2 mil PET/ss: 20 min bond	72 oz/inch
350°F Shear, 1" x1" x 1,000 gr., 2 mil PET/ss: 20 min bond	> 24 hours
Continuous operating temperature range	-40°F to 350°F (-54°C to 177°C)

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**