


**NT-905GFCW76 GLASS FILLED ACRYLIC TRANSFER ADHESIVE TAPE**

**NT-905GFCW76 is a glass filled solvent acrylic transfer PSA for use in various splicing and transfer adhesive applications.**

**FEATURES & BENEFITS**

- High adhesion
- Excellent low temp application performance
- Moderate shear strength

**CONSTRUCTION DIAGRAM**



**CONSTRUCTION**

5.5 mil white polycoated 76# kraft liner

5 mil glass filled acrylic adhesive

Self wound transfer adhesive

**TYPICAL APPLICATIONS**

- Die cutting
- Precision component assembly
- Graphic Arts
- Splicing

**PERFORMANCE**

| PROPERTIES  | NT-905GFCW76 |
|---|--------------|
| 180° Peel, 2 mil PET/ss: 10 min bond              | 50 oz/inch   |
| 180° Peel, 2 mil PET/ss: 72 hr dwell              | 90 oz/inch   |
| Shear, 1" x 1" x 1000g, 2 mil PET/ss: 10 min bond | 24+ H        |

**IMPORTANT NOTICE TO PURCHASER:** All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**

©2009 Adhesive Applications, Inc.