


NT 988 | 4 MIL CLEAR ACRYLIC TRANSFER ADHESIVE TAPE | TRANSFER ADHESIVE TAPES

NT-988 features a modified acrylic pressure sensitive transfer adhesive with excellent initial tack and shear strength. The adhesive is supplied on a moisture stable liner and has a smooth surface for faster substrate wet out. With the poly-coated kraft liner, NT 988 can be used for kiss cut applications, photo mounting and precision component assembly.

FEATURES & BENEFITS

- High initial tack
- Fast wet out
- Bonds well to low surface energy materials – polyethylene and polypropylene

CONSTRUCTION DIAGRAM



TYPICAL APPLICATIONS

- Mounting / graphic arts
- Die cutting
- Flying splice

CONSTRUCTION

PERFORMANCE

5.5 mil white 76# poly-coated kraft liner
4 mil modified acrylic adhesive
Self wound

180° Peel PET/ss: 20 min bond	104 oz/inch
Polyken Probe Tack	>1000 gr

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**

©2009 Adhesive Applications, Inc.