

# X20007

## PRELIMINARY PRODUCT DATA SHEET

### PRODUCT DESCRIPTION


#### Single Coated Tape

X20007 is a self-wound repulpable tape designed for splicing of various paper grades. The product consists of a 4.5 mil paper backing with 2.0 mils of a high tack acrylic adhesive.

### FEATURES & BENEFITS

- Superior adhesion to a variety of paper grades
- Great tensile strength
- Low VOC adhesive
- Repulpable paper backing

### PRODUCT CONSTRUCTION



### PRODUCT SPECIFICATIONS

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness (Total)	6.50 mils	0.165 mm	PSTC-133
Adhesive Thickness	2.00 mils	0.051 mm	PSTC-133
Carrier Thickness	4.50 mils	0.114 mm	PSTC-133
Peel Adhesion	50 oz/in	13.89 N/25mm	PSTC-101
Tack	50 oz	1418 g	ASTM D 2979
Shear Adhesion	24 hrs @ 2.2 psi	24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	40 lb/in	175 N/25mm	PSTC-131
Elongation	0 %	0 %	
Minimum Service Temperature	-20 °F	-29 °C	
Maximum Service Temperature	220 °F	104 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

### Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street  
Easthampton, MA 01027

413-527-7120 Main  
800-356-3572 Toll Free U.S.

[www.adhesiveapps.com](http://www.adhesiveapps.com)

**Adhesive**  
Applications™

Rev

