

A5302G

GREEN ACRYLIC ADHESIVE PROTECTIVE FILM

PRODUCT DESCRIPTION


Single Coated Tape

A5302G is a single-coated, self-wound transparent polyester (PET) film coated with a green removable acrylic adhesive. The product removes easily without adhesive residue. A5302G is well suited for use as a carrier in die cutting processes.

FEATURES & BENEFITS

- Controlled low adhesion level
- Clean removal / no adhesive residue
- Strong, abrasion resistant film backing
- Green color for easy visual identification

PRODUCT CONSTRUCTION



PRODUCT SPECIFICATIONS

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness (Total)	3.75 mils	0.095 mm	PSTC-133
Adhesive Thickness	0.75 mils	0.019 mm	PSTC-133
Carrier Thickness	3.00 mils	0.076 mm	PSTC-133
Peel Adhesion	8 oz/in	2.22 N/25mm	PSTC-101
Tack	11 oz	312 g	ASTM D 2979
Shear Adhesion	168 hrs @ 2.2 psi	168 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	75 lb/in	328 N/25mm	PSTC-131
Elongation	150 %	150 %	
Minimum Service Temperature	-20 °F	-29 °C	
Maximum Service Temperature	250 °F	121 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

Rev

11/26/2019

